

Micron Eagle Hydraulics Inc
 1291 N Post Oak Road
 Suite 170
 Houston
 TX 77055
 USA
 Tel: +1 713 812 0720



Micron Eagle Hydraulics Ltd
 Blackburn Industrial Estate
 Kinellar
 Aberdeen
 AB21 0RX
 Scotland UK
 Tel: +44 (0) 1224 790970

SPECIFICATION SHEET

HYPRO FILTRATION CART I.D. – MEH FC0101



Benefits

- Ideal for high viscosity lubrication and hydraulic oils
- Filter new fluids during transfer and replenishment
- Flush fluids already in service with high efficiency elements in addition to existing filtration
- Large Elements yields extended life (3, 6 or 10µ abs filter elements available)
- 150µ inlet filter element fitted for pump protection

Technical Specification

Max working pressure	6.8 bar
Max Flow	37 l/min
Electrical requirements	440-480V AC, 3ph, 50/60Hz, 16 amp socket
Max oil viscosity	500 cSt
Fluid compatibility	Petroleum and mineral based fluids.
Safety Valve	Pump internal relief valve fitted
Frame	Trolley mounted
Hydraulic Connections	1" BSP Male
Hoses	Can be supplied to suit client requirements
Dims/Weight	H 145cm, W 71cm, D 76cm : 164 Kg (Dry)

UNIT CAN BE CONFIGURED TO SUIT CLIENT REQUIREMENTS PRIOR TO MOBILISATION, PLEASE CONTACT MICRON EAGLE HYDRAULICS FOR FURTHER INFORMATION AND AVAILABILITY