

Micron Eagle Hydraulics Inc
 1291 N Post Oak Road
 Suite 170
 Houston
 TX 77055
 USA
 Tel: +1 713 812 0720



Micron Eagle Hydraulics Ltd
 Blackburn Industrial Estate
 Kinellar
 Aberdeen
 AB21 0RX
 Scotland UK
 Tel: +44 (0) 1224 790970

SPECIFICATION SHEET

HY-PRO VAC-U-DRY VACUUM DEHYDRATION SKID. – V10-D



Benefits

- Remove free and dissolved water down to 20 PPM
- High water removal efficiency
- Condensate water holding tank with automatic drain standard for 24/7 unattended operation
- High efficiency particulate filtration (3, 6, or 10µ abs elements available)
- Increased life of system components

Technical Specification

Flow rate	38 L/min
Max Discharge Pressure)	5.8 bar
Electric Requirements	415 VAC, 3 ph , 40 amps
Heater	2 x 12kw
Max oil viscosity	Up to 680cst
Hydraulic Connections	Connection In 16 JIC Male; Connection out 12 JIC Male (can be modified to suit client requirements)
Hoses	Can be supplied to suit client requirements
Dims/Weight	1829 x 1016 x 1905 mm / 1100kg Unit is moveable on castor wheels but no lifting points, supplied in wooden crate.

UNIT CAN BE CONFIGURED TO SUIT CLIENT REQUIREMENTS PRIOR TO MOBILISATION, PLEASE CONTACT MICRON EAGLE HYDRAULICS FOR FURTHER INFORMATION AND AVAILABILITY